

Product information

megol Motorenoel Mobility SAE 5W-30



Description

Motor oil based on Low-SAPS technology. Specially tailored to suit the requirements of modern exhaust aftertreatment systems. Specially developed for passenger car diesel engines from Renault. Ensures maximum service life of the diesel particulate filter as well as low wear, good engine cleanliness and long oil change intervals.

Area of application: Passenger cars.

SAPS level: Low-SAPS.

Note the manufacturer's instructions!

Specifications / Approvals

ACEA C4 • Renault RN 0720

Meguin recommends this product for vehicles or assemblies for which the following specifications or original part numbers are required:

Fiat 9.55535-S4

Characteristic data

SAE class (engine oils)	5W-30 SAE J300
Density at 15 °C	0,85 g/cm ³ DIN 51757
Viscosity at 40 °C	70 mm ² /s ASTM D 7042-04
Viscosity at 100 °C	12 mm ² /s ASTM D 7042-04
Viscosity at -35 °C (MRV)	< 60000 mPas ASTM D4684
Viscosity at -30 °C (CCS)	≤ 6600 mPas ASTM D5293
Viscosity index	169 DIN ISO 2909
HTHS at 150°C	≥ 3,5 mPas ASTM D5481
Pour point	-39 °C DIN ISO 3016
Evaporation loss (Noack)	9,2 % CEC-L-40-A-93
Flash point	220 °C DIN ISO 2592
Total base number	7,6 mg KOH/g DIN ISO 3771
Sulfate ash	≤ 0,5 g/100g DIN 51575
Color number (ASTM)	L3,0 DIN ISO 2049

Available pack sizes

1 l Canister plastic	3185 AR-DE-EN-ES-FR-IT-PT-RO-RU
5 l Canister plastic	3182 AR-DE-EN-ES-FR-IT-PT-RO-RU
20 l Canister plastic	9468 DE-EN
60 l Black plate barrel	9469 DE-EN
200 l Black plate barrel	9470 DE-EN
1 l Bulk goods	9454 DE

Available pack sizes