

Product information

megol Getriebeoel ATF Variable Low Viscosity



Description

Next-generation automatic transmission fluid based on HC synthetic base oils combined with advanced, high-performance additives. With its low viscosity, this fluid allows for optimal shifting under all operating conditions. Meets the requirements of many global automatic transmission and vehicle manufacturers.



Note manufacturer's instructions!

Meguin recommends this product for vehicles or assemblies for which the following specifications or original part numbers are required:

Aisin Warner AW-1 • BMW M-1375.4 • Dexron VI • Fiat 9.55550-AV5 • Ford Mercon LV • JWS 3324 (Aisin Warner) • Honda ATF 3.1 • Hyundai SP-IV • Mazda ATF FZ • MB 236.12 • MB 236.14 • Nissan AT-Matic S Fluid • Toyota WS • VW G 055 005 • VW G 055 540 • VW G 060 162

Characteristic data

Density at 15 °C	0,845 g/cm ³ DIN 51757
Viscosity at 40 °C	27,5 mm ² /s ASTM D 7042-04
Viscosity at 100 °C	5,7 mm ² /s ASTM D 7042-04
Viscosity at -40 °C (Brookfield)	≤ 15000 mPas ASTM D 2983-09
Viscosity index	155 DIN ISO 2909
Pour point	-48 °C DIN ISO 3016
Flash point	210 °C DIN ISO 2592
Color / appearance	braun/brown

Application

Shake well before use.

Available pack sizes

1 l Can plastic	33007 AR-DE-EL-EN-FR-RU
20 l Canister plastic	33010 DE-EN
200 l Black plate barrel	33084 DE-EN
1.000 l Container	33035 DE-EN