

Product information

megol Motorenoel New Engine FED SAE 0W-30



Description

High-performance motor oil based on synthetic base oils and modern Low-SAPS additive technology. Specially developed to meet the requirements of the latest Euro 6 diesel engines from Ford, as well as certain gasoline engines. Keeps the engine exceptionally clean and prevents premature clogging of the diesel particulate filter. Selected anti-wear additives ensure minimal friction. Also suitable for vehicles with automatic start-stop system.

Application: Passenger cars

SAPS level: Low-SAPS

Note manufacturer's instructions!

Specifications / Approvals

ACEA C2 • API SN • Ford WSS-M2C 950-A • Jaguar / Land Rover STJLR.03.5007 • VWC 53035

Characteristic data

Viscosity SAE class	0W-30 SAE J300
Density at 15 °C	0,85 g/cm ³ DIN 51757
Viscosity at 40 °C	49 mm ² /s ASTM D 7042-04
Viscosity at 100 °C	9,5 mm ² /s ASTM D 7042-04
Viscosity at -40 °C (MRV)	< 60000 mPas ASTM D 4684
Viscosity at -35 °C (CCS)	< 6200 mPas ASTM D 5293
HTHS at 150°C	> 2,9 mPas ASTM D 5481
Viscosity index	185 DIN ISO 2909
Pour point	-42 °C DIN ISO 3016
Flash point	220 °C DIN ISO 2592
Evaporation loss (Noack)	12 % ASTM 5800B
Total base number	7,7 mg KOH/g DIN ISO 3771
Sulfate ash	0,8 g/100g DIN 51575
Color number (ASTM)	L 2,5 DIN ISO 2049

Characteristic data

Oil base

Advanced Full Synthetic

Available pack sizes

1 l Canister plastic	33015 AR-DE-EN-ES-FR-IT-PT-RO-RU
5 l Canister plastic	33030 AR-DE-EN-ES-FR-IT-PT-RO-RU
20 l Canister plastic	33012 DE-EN
60 l Black plate barrel	33013 DE-EN
200 l Black plate barrel	33014 DE-EN
1.000 l Deposit container	33016 DE-EN