

Product information

megol Getriebeoel ATF Variable gelb



Description

The next generation of automatic transmission fluid based on HC synthetic base oils in combination with state-of-the-art, powerful additives. It meets the requirements of a large number of global automatic transmission and vehicle manufacturers. megol ATF Variable Yellow automatic transmission fluid is suitable for use in automatic transmissions, manual transmissions, clutch and steering systems, hydraulic systems and auxiliary drives in both passenger cars and commercial vehicles.



Available pack sizes

200 l Black plate barrel 33085
DE-EN

Meguin recommends this product for vehicles or assemblies for which the following specifications or original part numbers are required:

Allison C4 • Allison TES 295 • BMW 7045 E • BMW 8072 B • BMW LA 2634 • BMW LT 71141 • Caterpillar TO-2 • Chrysler ATF +3 • Chrysler ATF +4 • Daimler NAG-1 • Dexron III H • Ford Mercon V • Honda ATF Z1 (except CVT) • Hyundai SP-III • Hyundai SP-II • JASO 1-A • JWS 3309 (Aisin Warner) • Kia SP-II • Kia SP-III • MAN 339 Typ V1 • MAN 339 Typ Z2 • MAN 339 Typ Z1 • Mazda ATF M-V • Mazda ATF M-III • MB 236.2 • MB 236.5 • MB 236.6 • MB 236.7 • MB 236.9 • MB 236.10 • MB 236.11 • MB 236.91 • Mitsubishi SP-II • Mitsubishi SP-III • Nissan AT-Matic D Fluid • Nissan AT-Matic J Fluid • Nissan AT-Matic K Fluid • Subaru ATF • Toyota Type T-III • Toyota Type T-IV • Volvo 97341 • Volvo 97340 • Voith H55.6335.XX (G 607) • VW G 052 990 • VW G 055 025 • ZF TE-ML 02F • ZF TE-ML 03D • ZF TE-ML 04D • ZF TE-ML 05L • ZF TE-ML 09 • ZF TE-ML 11A • ZF TE-ML 11B • ZF TE-ML 14A • ZF TE-ML 14B • ZF TE-ML 17C • AE (LT 71141)

Characteristic data

Density at 15 °C	0,850 g/cm ³ DIN 51757
Viscosity at 40 °C	36,9 mm ² /s ASTM D 7042-04
Viscosity at 100 °C	7,0 mm ² /s ASTM D 7042-04
Viscosity at -40 °C (Brookfield)	<= 20000 mPas ASTM D 2983-09
Viscosity index	150 DIN ISO 2909
Pour point	-45 °C DIN ISO 3016
Flash point	218 °C DIN ISO 2592
Color number (ASTM)	L 2,0 DIN ISO 2049

Available pack sizes