

Product information

megol Motorenoel Premium ECO SAE 0W-20



Description

Premium motor oil with outstanding performance. Produced on the basis of the best raw materials and the very latest technologies. Provides excellent lubricating film, aging and shear stability, optimum wear protection and maximum engine cleanliness. Specially developed for modern Ford gasoline and diesel engines. Ensures smooth engine operation under all temperature and operating conditions.

Application: Passenger cars

SAPS level: Low-SAPS

Note manufacturer's instructions!

Specifications / Approvals

ACEA C5 • API SQ • Ford WSS-M2C 952-A1

Meguin recommends this product for vehicles or assemblies for which the following specifications or original part numbers are required:

MB 229.71 • Opel OV 040 1547 - A20

Characteristic data

SAE class (engine oils)	0W-20 SAE J300
Density at 15 °C	0,845 g/cm ³ DIN 51757
Viscosity at 40 °C	39 mm ² /s ASTM D 7042-04
Viscosity at 100 °C	8 mm ² /s ASTM D 7042-04
Viscosity at -40 °C (MRV)	< 60000 mPas ASTM D 4684
Viscosity at -35 °C (CCS)	≤ 6200 mPas ASTM D 5293
Viscosity index	185 DIN ISO 2909
HTHS at 150°C	≥ 2,6 mPas ASTM D 5481
Pour point	-42 °C DIN ISO 3016
Evaporation loss (Noack)	11 % CEC-L-10-A-93
Flash point	220 °C DIN ISO 2592
Total base number	9,5 mg KOH/g DIN ISO 3771
Sulfate ash	≤ 0,8 % DIN 51575
Color number (ASTM)	L 3,0 DIN ISO 2049

Available pack sizes

1 l Canister plastic	33114 AR-DE-EN-ES-FR-IT-PT-RO-RU
5 l Canister plastic	33115 AR-DE-EN-ES-FR-IT-PT-RO-RU
20 l Canister plastic	33116 DE-EN
60 l Black plate barrel	33117 DE-EN
200 l Black plate barrel	33118 DE-EN
1.000 l Deposit container	33119 DE-EN