

Product information

megol Motorenoel Racing 4T SAE 20W-50



Description

Modern motor oil specifically for use in four-stroke engines of two-wheel vehicles. The combination of synthetic and mineral base oils with advanced additive technology protects the engine in the best possible manner against wear and has proven itself particularly in the use in two-wheel four-stroke engines under high thermal stress.

Specifications / Approvals

API SP • JASO MA2

Characteristic data

SAE class (engine oils)	20W-50 SAE J300
Density at 15 °C	0,875 g/cm ³ DIN 51757
Viscosity at 40 °C	156,0 mm ² /s ASTM D 7042-04
Viscosity at 100 °C	18,0 mm ² /s ASTM D 7042-04
Viscosity index	128 DIN ISO 2909
Viscosity at -15 °C (CCS)	<= 9500 mPas ASTM D 5293
HTHS at 150°C	≥ 3,7 mPas ASTM D 5481
Pour point	-33 °C DIN ISO 3016
Evaporation loss (Noack)	7,9 % ASTM D 5800
Flash point	240 °C DIN ISO 2592
Total base number	7,0 mg KOH/g DIN ISO 3771
Sulfate ash	0,8 g/100g DIN 51575
Color number (ASTM)	L 2,0 DIN ISO 2049

Available pack sizes

5 l Canister plastic	33157 AR-DE-EN-ES-FR-IT-PT-RO- RU
20 l Canister plastic	6514 DE-EN