

Product information

megol Motorenoel Racing 4T SAE 10W-40



Description

High-performance motor oil with ideal properties for both air and water-cooled four-stroke motorcycle engines. Thanks to special base oil components and additives, it provides excellent lubricity, optimal engine cleanliness, and good cold-start performance. Suitable for year-round use under normal and difficult conditions.

Note manufacturer's instructions!

Specifications / Approvals

API SP • JASO MA2

Characteristic data

SAE class (engine oils)	10W-40 SAE J300
Density at 15 °C	0,860 g/cm ³ DIN 51757
Viscosity at 40 °C	96,0 mm ² /s ASTM D 7042-04
Viscosity at 100 °C	14,6 mm ² /s ASTM D 7042-04
Viscosity at -25 °C (CCS)	<= 7000 mPas ASTM D 5293
Viscosity index	158 DIN ISO 2909
HTHS at 150°C	≥ 3,5 mPas ASTM D 5481
Pour point	-36 °C DIN ISO 3016
Evaporation loss (Noack)	10,0 % ASTM D 5800-08 Method B
Flash point	238 °C DIN ISO 2592
Total base number	7,0 mg KOH/g DIN ISO 3771
Sulfate ash	0,8 g/100g DIN 51575
Color number (ASTM)	L 2,0 DIN ISO 2049
Oil base	Advanced Full Synthetic

Available pack sizes

20 l Canister plastic	9687 DE-ES-FR-IT-NL
60 l Black plate barrel	33158 DE-EN
200 l Black plate barrel	9688 DE-ES-FR-IT-NL
1 l Bulk goods	3522 DE

Available pack sizes

1 l Canister plastic	9609 AR-DE-EN-ES-FR-IT-PT-RO-RU
5 l Canister plastic	33159 AR-DE-EN-ES-FR-IT-PT-RO-RU