

Product information

megol Doppelkupplungsgetriebe Fluid



Description

High-performance gear oil that can be used in vehicles with dual-clutch transmissions (DCT) that require a special DCT fluid, e.g. VW, Audi, Seat, Škoda (Direct Shift Gearbox), Ford (Powershift), Chrysler, Volvo, etc. Only top quality HC synthetic base oils are used for the fluid in combination with an exclusive additive technology. This consistently guarantees stable friction characteristics, even under extreme conditions. Under no circumstances should this fluid be mixed with other dual clutch transmission fluids.



Note the manufacturer's instructions.

Meguin recommends this product for vehicles or assemblies for which the following specifications or original part numbers are required:

BMW DCTF-1 • BMW DCTF-1+ • Chrysler • Ford WSS-M2C 936-A • MB 236.21 • Mitsubishi Dia Queen • Peugeot Citroen (PSA) 9734.S2 • Porsche 999.917.080.00 • Volvo 1161838 • Volvo 1161839 • VW G 052 182 • VW G 052 529 • VW G 052 536 • VW G 055 529

Characteristic data

Density at 15 °C	0,845 g/cm ³ DIN 51757
Viscosity at 40 °C	31,5 mm ² /s ASTM D7042
Viscosity at 100 °C	6,6 mm ² /s ASTM D7042
Viscosity at -40 °C	<20000 mPas DIN 51398
Viscosity index	175 DIN ISO 2909
Pour point	-48 °C DIN ISO 3016
Flash point	200 °C DIN ISO 2592
Color / appearance	yellowish

Application

Shake well before use.

Available pack sizes

1 l Can plastic	3529 AR-DE-EL-EN-FR-RU
20 l Canister plastic	33053 DE-EN