

Product information

megol Hypoid-Getriebeöl GL 4+ SAE 75W-90



Description

Fully synthetic multi-grade gearbox oil with anti-corrosion and high pressure properties for low and high temperatures. Multipurpose transmission fluid with a wide range of applications in vehicle transmissions, primarily manual transmissions. At low temperatures, eliminates shifting problems and noise in manual transmissions. The fully synthetic base oils combined with advanced additive technology provide excellent wear protection under all operating conditions, in both summer and winter. Also suitable for Arctic climates.



Available pack sizes

1 l Bulk goods

9205

DE

Specifications / Approvals

API GL4+

Meguin recommends this product for vehicles or assemblies for which the following specifications or original part numbers are required:

Ford ESD-M2C 175-A • VW 501 50 (G50) • ZF TE-ML 08A • MIL-L 2105

Characteristic data

SAE class (gear oils)	75W-90 SAE J306
Density at 15 °C	0,855 g/cm ³ DIN 51757
Viscosity at 40 °C	94,0 mm ² /s ASTM D7042
Viscosity at 100 °C	15,5 mm ² /s ASTM D7042
Viscosity at -40 °C (Brookfield)	<= 150000 mPas ASTM D2983
Viscosity index	175 DIN ISO 2909
Pour point	-60 °C DIN ISO 3016
Flash point	200 °C DIN ISO 2592
Color number (ASTM)	L 1,5 DIN ISO 2049

Available pack sizes

1 l Can plastic	3535 DE-EL-EN-FR-HR-RU
20 l Canister plastic	8616 DE-EN
60 l Black plate barrel	6668 DE-EN
200 l Black plate barrel	8618 DE-EN