

Product information

megol Hypoid-Getriebeöl GL 5 SAE 75W-140 LS



Description

Fully synthetic gear oil with LS additive (LS = limited slip) for use in passenger cars, preferably in BMW vehicles with locked axle systems and in axles, manual transmissions and ancillary units with extended oil change intervals in commercial vehicles (trucks, construction machinery, agricultural units). megol Hypoid Gear Oil GL 5 SAE 75W-140 LS is suitable for the wide temperature range thanks to the set SAE Class.



Specifications / Approvals

API GL5 • VME

Meguin recommends this product for vehicles or assemblies for which the following specifications or original part numbers are required:

BMW rear-axle gear oil • Ford WSL-M2C 192-A • Scania STO 1:0 • ZF TE-ML 05D • ZF TE-ML 12D • ZF TE-ML 16G

Characteristic data

SAE class (gear oils)	75W-140 SAE J306
Density at 15 °C	0,875 g/cm ³ DIN 51757
Viscosity at 40 °C	179 mm ² /s ASTM D 7042-04
Viscosity at 100 °C	25 mm ² /s ASTM D 7042-04
Viscosity at -40 °C (Brookfield)	<= 150000 mPas ASTM D 2983-09
Viscosity index	172 DIN ISO 2909
Pour point	-51 °C DIN ISO 3016
Flash point	208 °C DIN ISO 2592
Color number (ASTM)	L 1,5 DIN ISO 2049

Available pack sizes

1 l Can plastic 3536
DE-EL-EN-FR-HR-RU