

Product information

megol Motorenoel HD Super Turbo SAE 15W-40



Description

Multigrade motor oil for year-round use. For diesel and gasoline engines for which a multigrade oil compliant with API SF/CF is specified. Its package of additives ensures optimum wear protection and engine cleanliness.

Range of applications: Passenger cars (youngtimers), light commercial vehicles, older agricultural and construction machinery.

SAPS level: High-SAPS.

Note the manufacturer's instructions!

Specifications / Approvals

API CD • API SF

Characteristic data

SAE class (engine oils)	15W-40 SAE J300
Density at 15 °C	0,875 g/cm ³ DIN 51757
Viscosity at 40 °C	109 mm ² /s ASTM D 7042-04
Viscosity at 100 °C	14,3 mm ² /s ASTM D 7042-04
Viscosity at -25 °C (MRV)	< 60000 mPas ASTM D4684
Viscosity at -20 °C (CCS)	< 7000 mPas ASTM D5293
Viscosity index	133 DIN ISO 2909
HTHS at 150°C	> 3,7 mPas ASTM D5481
Pour point	-30 °C DIN ISO 3016
Evaporation loss (Noack)	13 % CEC-L-40-A-93
Flash point	230 °C DIN ISO 2592
Total base number	6,5 mg KOH/g DIN ISO 3771
Sulfate ash	0,65 g/100g DIN 51575
Color number (ASTM)	4 DIN ISO 2049

Available pack sizes

1 l Canister plastic	4373 AR-DE-EN-ES-FR-IT-PT-RO-RU
5 l Canister plastic	1670 AR-DE-EN-ES-FR-IT-PT-RO-RU
20 l Canister plastic	1671 DE-EN
200 l Black plate barrel	1673 DE-EN

Available pack sizes