

Product information

megol Hypoid-Getriebeöl GL 5 SAE 75W-90 (vollsynth.)



Description

Fully synthetic multigrade gear oil with corrosion protection and high-pressure properties for low and high temperatures. Friction reduction contributes to fuel savings. A hypoid gear oil with a broad application range in vehicle transmissions, including manual transmissions, if GL 5 oils are approved. Starting and shifting problems as well as noise development in manual transmissions are eliminated at low temperatures. Due to the fully synthetic base oils in combination with modern additive technology, this lubricant guarantees outstanding wear protection under all operating conditions in summer and winter operation.

Available pack sizes

60 l Black plate barrel 4652
DE-EN

Specifications / Approvals

API GL5

Meguin recommends this product for vehicles or assemblies for which the following specifications or original part numbers are required:

MIL-L 2105 D • MIL-L 2105 C

Characteristic data

SAE class (gear oils)	75W-90 SAE J306
Density at 15 °C	0,855 g/cm ³ DIN 51757
Viscosity at 40 °C	80 mm ² /s ASTM D 7042-04
Viscosity at 100 °C	14,3 mm ² /s ASTM D 7042-04
Viscosity at -40 °C (Brookfield)	<= 150000 mPas ASTM D 2983-09
Viscosity index	185 DIN ISO 2909
Pour point	-57 °C DIN ISO 3016
Flash point	190 °C DIN ISO 2592
Color number (ASTM)	L 1,0 DIN ISO 2049

Available pack sizes

1 l Can plastic	4650 DE-EL-EN-FR-HR-RU
1 l Can plastic	9637 AR-EN-ES-FR-NL-PT
20 l Canister plastic	4651 DE-EN