

Product information

megol Hypoid-Getriebeoel GL 5 SAE 85W-90 LS



Description

A high-quality hypoid gear oil which has been developed for use under the extreme conditions which are encountered especially in vehicles with **limited slip differential**. It contains special additives, which in addition to outstanding EP properties also mean that the oil is capable of altering the frictional coefficient between the clutch plates in such a way as to prevent stick-slip and its consequential judder. The product therefore satisfies the special requirements of all reputable motor vehicle manufacturers for limited slip differentials.

Available pack sizes

1 l Bulk goods

9207
DE

Specifications / Approvals

API GL5

Meguin recommends this product for vehicles or assemblies for which the following specifications or original part numbers are required:

DAF • GM B 40 1010 • MIL-L 2105 D • Volvo 97311 •
Volvo (Axles/limited slip differential) • ZF TE-ML 05C

Characteristic data

SAE class (gear oils)	85W-90 SAE J306
Density at 15 °C	0,9 g/cm ³ DIN 51757
Viscosity at 40 °C	195 mm ² /s ASTM D 7042-04
Viscosity at 100 °C	17,8 mm ² /s ASTM D 7042-04
Viscosity at -12 °C (Brookfield)	<= 150000 mPas ASTM D 2983-09
Viscosity index	99 DIN ISO 2909
Pour point	-18 °C DIN ISO 3016
Flash point	220 °C DIN ISO 2592
Color number (ASTM)	3,5 DIN ISO 2049

Available pack sizes

20 l Canister plastic	4654 DE-EN
60 l Black plate barrel	4655 DE-EN
200 l Black plate barrel	4873 DE-EN
1.000 l Deposit container	9530 DE-EN