

Product information

megol Motorenoel HD-C3 SG (single-grade) SAE 30



Description

Single-grade motor oil with naturally high viscosity index. Because of its special properties, particularly suitable for use in diesel engines under extreme operating conditions. Its high alkaline reserve reliably prevents corrosion.

Note the manufacturer's instructions!

Specifications / Approvals

ACEA E2 • API SJ • API CF • API CF-4

Meguin recommends this product for vehicles or assemblies for which the following specifications or original part numbers are required:

MAN 270 • MB 228.0 • Volvo VDS

Available pack sizes

60 l Black plate barrel	4686 DE-EN
200 l Black plate barrel	4849 DE-EN
1 l Bulk goods	6883 DE

Characteristic data

SAE class (engine oils)	30 SAE J300
Density at 15 °C	0,875 g/cm ³ DIN 51757
Viscosity at 40 °C	90 mm ² /s ASTM D 7042-04
Viscosity at 100 °C	11,6 mm ² /s ASTM D 7042-04
Viscosity index	115 DIN ISO 2909
Pour point	-33 °C DIN ISO 2592
Evaporation loss (Noack)	6,8 % ASTM D 5800-08 Method B
Flash point	230 °C DIN ISO 3016
Total base number	11 mg KOH/g DIN ISO 3771
Sulfate ash	1,2 g/100g DIN 51575
Color number (ASTM)	4 DIN ISO 2049

Available pack sizes

1 l Canister plastic	4683 AR-DE-EN-ES-FR-IT-PT-RO-RU
20 l Canister plastic	4685 DE-EN