

Product information

Meguin Fließfett L00



Description

Flow grease based on lithium soap with highly effective additive packages.

Properties

Thanks to highly effective additive packages, extremely resistant to aging with very good corrosion and wear protection properties. Ensures a long service life, thereby helping to save maintenance costs.

Operating temperature range

-40 °C to +120 °C

Meguin recommends this product for vehicles or assemblies for which the following specifications or original part numbers are required:

DTFR 33B100 (264.0) • MAN 283 Li • Willy Vogel

Characteristic data

Brief description	K00/000K-40 DIN 51502
Operating temperature range	-40 bis +120
NLGI number	00/000 DIN 51818
Thickener	Lithiumseife
Worked penetration	400-460 1/10 mm DIN ISO 2137
Dropping point	165 °C DIN ISO 2176
Color / appearance	grün
Flow pressure at -40 °C	<1400 mbar DIN 51805
Emcor corrosion class	0/0 DIN 51802
Copper corrosion after 24 hours at 100 °C	1 b DIN 51811
Behavior in the presence of water	1-90 DIN 51807 Teil 1
Base oil	Mineralöl
Viscosity at 40 °C	45,0 mm ² /s ASTM D 7042-04
Flash point	184 °C DIN ISO 2592
Pour point	-36 °C DIN ISO 3016

Specially recommended for use in central lubrication systems on commercial vehicles.

Available pack sizes

900 g Bag plastic	33155 D-GB
5 kg Bucket plastic	4690 D-GB
25 kg Bucket plastic	4692 D-GB
50 kg Bucket black plate	6673 D-GB
180 kg Black plate barrel	4864 D-GB



Application

Is particularly suitable for lubricating roller and plain bearings under normal load with low to medium speeds, even under dusty and damp conditions.