

Product information

megol Motorenoel Universal SAE 15W-40



Description

Multigrade motor oil for year-round use. Ideal lubricant for gasoline engines with and without catalytic converter and for diesel engines, including those with a turbocharger. Its additive packages provide extraordinary protection against wear and keep the engine clean.

Range of applications: Passenger cars, trucks, construction and agricultural machinery.

SAPS level: High-SAPS.

Note the manufacturer's instructions!

Specifications / Approvals

ACEA A2, B3, E2 • API SJ • API CF-4 • MIL-L 2104 E • MIL-L 46152 D

Meguin recommends this product for vehicles or assemblies for which the following specifications or original part numbers are required:

Allison C4 • Caterpillar TO-2 • MAN 271 • MB 228.1 • MTU Typ 1 • Volvo VDS

Characteristic data

SAE class (engine oils)	15W-40 SAE J300
Density at 15 °C	0,875 g/cm ³ DIN 51757
Viscosity at 40 °C	103,0 mm ² /s ASTM D 7042-04
Viscosity at 100 °C	14,2 mm ² /s ASTM D 7042-04
Viscosity at -25 °C (MRV)	< 60000 mPas ASTM D4684
Viscosity at -20 °C (CCS)	≤ 7000 mPas ASTM D5293
Viscosity index	140 DIN ISO 2909
HTHS at 150°C	≥ 3,7 mPas ASTM D5481
Pour point	-33 °C DIN ISO 3016
Evaporation loss (Noack)	9,2 % CEC-L-40-A-93
Flash point	230 °C DIN ISO 2592
Total base number	9 mg KOH/g DIN ISO 3771
Sulfate ash	1,1 % DIN 51575

Characteristic data

Color number (ASTM)	L 2,5 DIN ISO 2049
---------------------	-----------------------

Available pack sizes

1 l Canister plastic	4696 AR-DE-EN-ES-FR-IT-PT-RO-RU
4 l Canister plastic	9149 AR-DE-EN-ES-FR-IT-PT-RO-RU
5 l Canister plastic	4689 D-GB-F-ARAB-RUS-RO-I-E-P
5 l Canister plastic	33079 DE-DZAR-EN-FR
20 l Canister plastic	4678 DE-EN
60 l Black plate barrel	4844 DE-EN
200 l Black plate barrel	4845 DE-EN