

Product information

megol Motorenoel Power Synt SAE 10W-40



Description

Premium low-friction motor oil. Its combination of high-tech fluids, modern additive technology and synthetic components allows it to be used year-round in gasoline and diesel engines with and without turbochargers. Improves engine performance and reduces friction. To ensure full performance, avoid mixing with other motor oils.

Application: Passenger cars

SAPS level: High-SAPS

Note manufacturer's instructions!

Specifications / Approvals

ACEA A3 • ACEA B4 • API CF • API SN

Meguin recommends this product for vehicles or assemblies for which the following specifications or original part numbers are required:

MB 229.3 • VW 502 00 • VW 505 00

Characteristic data

SAE class (engine oils)	10W-40 SAE J300
Density at 15 °C	0,865 g/cm ³ DIN 51757
Viscosity at 40 °C	91 mm ² /s ASTM D 7042-04
Viscosity at 100 °C	14 mm ² /s ASTM D 7042-04
Viscosity at -30 °C (MRV)	< 60000 mPas ASTM D4684
Viscosity at -25 °C (CCS)	<= 7000 mPas ASTM D5293
Viscosity index	158 DIN ISO 2909
HTHS at 150°C	>= 3,5 mPas ASTM D5481
Pour point	-39 °C DIN ISO 3016
Evaporation loss (Noack)	9,7 % CEC-L-40-A-93
Flash point	234 °C DIN ISO 2592
Total base number	8,2 mg KOH/g DIN ISO 3771
Sulfate ash	1,0 - 1,6 g/100g DIN 51575

Characteristic data

Color number (ASTM)	L4,0
	DIN ISO 2049

Available pack sizes

1 l Canister plastic	4804 AR-DE-EN-ES-FR-IT-PT-RO-RU
4 l Canister plastic	4364 AR-DE-EN-ES-FR-IT-PT-RO-RU
5 l Canister plastic	4800 AR-DE-EN-ES-FR-IT-PT-RO-RU
20 l Canister plastic	4805 DE-EN
60 l Black plate barrel	4806 DE-EN
200 l Black plate barrel	4807 DE-EN