

Product information

megol Hypoid-Getriebeöl TDL SAE 75W-90 (teilsynth.)



Description

Part-synthetic multigrade transmission fluid for universal use. Meets virtually all the requirements that modern commercial vehicles, in particular, place on lubricants for the entire drive line. As a TDL (total drive line) transmission fluid, it is ideally suited for lubricating all drivetrain components, from heavy-duty synchronized and non-synchronized manual transmissions to hypoid final drives. By reducing the number of oil types required and eliminating the risk of using the wrong oil, it significantly streamlines operations in modern vehicle fleets.

Available pack sizes

200 l Black plate barrel 4836
DE-EN

Specifications / Approvals

API GL4 • API GL5 • API MT-1

Meguin recommends this product for vehicles or assemblies for which the following specifications or original part numbers are required:

DAF • Eaton • MAN M 3343 Typ M • Scania ST0 1:0 • ZF TE-ML 02B • ZF TE-ML 08 • ZF TE-ML 12B • ZF TE-ML 16B • ZF TE-ML 17B • ZF TE-ML 19B

Characteristic data

SAE class (gear oils)	75W-90 SAE J306
Density at 15 °C	0,875 g/cm ³ DIN 51757
Viscosity at 40 °C	80,0 mm ² /s ASTM D 7042-04
Viscosity at 100 °C	14,2 mm ² /s ASTM D 7042-04
Viscosity at -40 °C (Brookfield)	<= 150000 mPas ASTM D 2983-09
Viscosity index	180 DIN ISO 2909
Pour point	-48 °C Din ISO 3016
Flash point	180 °C DIN ISO 2592
Color number (ASTM)	L 2,0 DIN ISO 2049

Available pack sizes

20 l Canister plastic	4834 DE-EN
60 l Black plate barrel	4835 DE-EN