

Product information

megol Mehrzweckgetriebeöl GL 4 SAE 80W-90



Description

Multigrade gear oil with a wide range of applications with high stress across the tooth face. Gear oils of this type are recommended by automotive and transmission manufacturers, among other things for use in synchronized and non-synchronized manual transmissions, engines in construction equipment, agricultural machinery and tractor units.



Specifications / Approvals

API GL4

Meguin recommends this product for vehicles or assemblies for which the following specifications or original part numbers are required:

MAN 341 Typ Z1 • MIL-L 2105

Characteristic data

Density at 15 °C	0,895 g/cm ³ DIN 51757
Viscosity at 40 °C	143 mm ² /s ASTM D 7042-04
Viscosity at 100 °C	14,5 mm ² /s ASTM D 7042-04
Viscosity at -26 °C (Brookfield)	<= 150000 mPas ASTM D 2983-09
Viscosity index	100 DIN ISO 2909
Pour point	-30 °C DIN ISO 3016
Flash point	220 °C DIN ISO 2592
Color number (ASTM)	L3,0 DIN ISO 2049

Available pack sizes

1 l Can plastic	4866 DE-EL-EN-FR-HR-RU
20 l Canister plastic	4821 DE-EN
60 l Black plate barrel	4822 DE-EN
200 l Black plate barrel	4823 DE-EN
1.000 l Deposit container	9788 DE-EN