

Product information

megol Mehrzweckgetriebeöl GL 4 SAE 75W-90



Description

Semi-synthetic multigrade transmission fluid suitable for both low and high temperatures. Multipurpose transmission fluid with a wide range of applications in vehicle transmissions, primarily manual transmissions. At low temperatures, eliminates shifting problems and noise in manual transmissions.



Specifications / Approvals

API GL4

Meguin recommends this product for vehicles or assemblies for which the following specifications or original part numbers are required:

MIL-L 2105

Characteristic data

SAE class (gear oils)	75W-90 SAE J306
Density at 15 °C	0,875 g/cm ³ DIN 51757
Viscosity at 40 °C	86 mm ² /s ASTM D 7042-04
Viscosity at 100 °C	14,2 mm ² /s ASTM D 7042-04
Viscosity at -40 °C (Brookfield)	<= 150000 mPas ASTM D 2983-09
Viscosity index	171 DIN ISO 2909
Pour point	-45 °C DIN ISO 3016
Flash point	202 °C DIN ISO 2592
Oxide ash	0,1 g/100g DIN EN ISO 6245

Available pack sizes

1 l Can plastic	4867 DE-EL-EN-FR-HR-RU
20 l Canister plastic	4824 DE-EN
60 l Black plate barrel	4825 DE-EN