

Product information

megol Transmission Fluid ATF III



Description

Hydraulic fluid for automatic transmissions and hydraulic clutches for which a type Dexron III automatic transmission fluid is prescribed. It guarantees perfect operation of hydraulic transmissions even in the heaviest duty applications and even when exposed to large temperature fluctuations. Also suitable as a hydraulic fluid for systems that work under extreme operating conditions.

Note the manufacturer's instructions.



Specifications / Approvals

Caterpillar TO-2 • DTFR 13C100 H • MAN 339 Typ L1 • MAN 339 Typ V1 • MAN 339 Typ Z1 • MB-Approval 236.1 • Voith H55.6335.XX (G 607) • ZF TE-ML 03D • ZF TE-ML 04D • ZF TE-ML 14A • ZF TE-ML 17C • ZF approval number ZF004922

Available pack sizes

20 l Canister plastic	4876 DE-EN
60 l Black plate barrel	4659 DE-EN
200 l Black plate barrel	4862 DE-EN

Meguin recommends this product for vehicles or assemblies for which the following specifications or original part numbers are required:

Allison C4 • Allison TES 389 • Dexron II D • Dexron II E • Dexron III G • Dexron III H • TASA • Ford Mercon • MB 236.6 • Volvo 97341 • ZF TE-ML 02F • ZF TE-ML 09 • ZF TE-ML 11A • ZF TE-ML 11B • ZF TE-ML 14B

Characteristic data

Density at 15 °C	0,845 g/cm ³ DIN 51757
Viscosity at 40 °C	36,0 mm ² /s ASTM D 7042-04
Viscosity at 100 °C	7,5 mm ² /s ASTM D 7042-04
Viscosity at -40 °C (Brookfield)	<= 20000 mPas ASTM D 2983-09
Viscosity index	180 DIN ISO 2909
Pour point	-48 °C DIN ISO 3016
Flash point	220 °C DIN ISO 2592
Sulfate ash	0,1 g/100g DIN 51575
Shear stability, viscosity at 100 °C after 100 h	5,4 mm ² /s DIN 51350-06-KRL/C
Color / appearance	red

Available pack sizes

1 l Can plastic	4875 DE-EL-EN-FR-HR-RU
-----------------	---------------------------