

Product information

megol Hypoid-Getriebeöl GL 5 SAE 85W-90



Description

High-quality motor vehicle gear oil for the most extreme conditions. Mandatory for axle drives with hypoid transmissions.

Specifications / Approvals

API GL5 • DTFR 12B100 • MB-Approval 235.0H • ZF TE-ML 07A • ZF TE-ML 16C • ZF TE-ML 17B • ZF TE-ML 19B • ZF TE-ML 21A • ZF approval number ZF000069

Meguin recommends this product for vehicles or assemblies for which the following specifications or original part numbers are required:

MAN 342 Typ M1 • MIL-L 2105 D

Characteristic data

SAE class (gear oils)	85W-90 SAE J306
Density at 15 °C	0,9 g/cm ³ DIN 51757
Viscosity at 40 °C	194 mm ² /s ASTM D 7042-04
Viscosity at 100 °C	17,5 mm ² /s ASTM D 7042-04
Viscosity at -12 °C (Brookfield)	<= 150000 mPas ASTM D 2983-09
Viscosity index	97 DIN ISO 2909
Pour point	-18 °C DIN ISO 3016
Flash point	210 °C DIN ISO 2592
Color number (ASTM)	L 4,0 DIN ISO 2049

Available pack sizes

20 l Canister plastic	4878 DE-EN
60 l Black plate barrel	4869 DE-EN
200 l Black plate barrel	4870 DE-EN
1 l Bulk goods	9086 DE