

Product information

Meguin Getriebefließfett NP00



Description

Flow grease based on sodium soap with highly effective additive packages.

Properties

Thanks to highly effective additive packages, extremely resistant to aging with very good corrosion and wear protection properties. Ensures a long service life, thereby helping to save maintenance costs.

Operating temperature range

-30 °C to +100 °C

Characteristic data

Brief description	GP00/000H-30 DIN 51502
Operating temperature range	-30 bis +100
NLGI number	00/000 DIN 51818
Thickener	Natriumseife
Worked penetration	425-455 1/10 mm DIN ISO 2137
Dropping point	>140 °C DIN ISO 2176
Color / appearance	naturfarben
Flow pressure at -25 °C	<140 mbar DIN 51805
Emcor corrosion class	0/0 DIN 51802
Copper corrosion after 24 hours at 100 °C	1 b DIN 51811
Behavior in the presence of water	3-90 DIN 51807 Teil 1
Base oil	Mineralöl
Viscosity at 40 °C	130,0 mm ² /s ASTM D 7042-04
Flash point	242 °C DIN ISO 2592
Pour point	-21 °C DIN ISO 3016

Available pack sizes

5 kg Bucket plastic	6318 DE-EN
25 kg Bucket plastic	8452 DE-EN
180 kg Black plate barrel	8454 DE-EN

Application

Is particularly suitable for the lubrication of closed transmissions and drum motors under low loads. Very good adhesion properties, which is of particular importance with fast-turning transmissions and gear motors.

Available pack sizes