

Product information

Meguin Mehrzweckfett L3



Description

Multi-purpose grease based on a lithium soap.

Properties

Resistant to aging, with good corrosion and wear protection properties.

Temperature range

-25 °C to +140 °C

Characteristic data

Brief description	K3N-25 DIN 51502
NLGI number	3 DIN 51818
Saponification type	Lithiumseife
Worked penetration	220-250 1/10 mm DIN ISO 2137
Dropping point	190 °C DIN ISO 2176
Oil separation after 18 hours at 40 °C	0,8 % DIN 51817
Oil separation after 7 days at 40 °C	1,7 % DIN 51817
Flow pressure at -25 °C	<1400 mbar DIN 51805
Emcor corrosion class	0/0 DIN 51802
Copper corrosion after 24 hours at 100 °C	1 b DIN 51811
Behavior in the presence of water	1-90 DIN 51807 Teil 1 Mineralöl
Viscosity at 40 °C	120,0 mm ² /s ASTM D 7042-04
Flash point	236 °C DIN ISO 2592
Pour point	-21 °C DIN ISO 3016

Available pack sizes

15 kg Bucket plastic	8798 D-GB
25 kg Bucket plastic	6444 D-GB
50 kg Bucket black plate	6660 D-GB
180 kg Black plate barrel	4623 D-GB

Application

Particularly suitable for the lubrication of normally stressed roller and plain bearings which operate at normal to high rotational speeds, also used under dusty and damp conditions. Its long shelf life and operating time guarantee economical use in a wide range of applications.

Available pack sizes

5 kg Bucket plastic	6493 D-GB
---------------------	--------------