

Product information

megol Zweitaktmotorenoel GD (vollsynthetisch)



Description

Two-stroke motor oil based on synthetic base oils and modern additive technology. Meets or exceeds the highest requirements for two-stroke engines for on-road and off-road use. Extremely low-smoke and residue-free combustion; protects engine and exhaust system against deposits. Thanks to its fully synthetic composition, thermally highly stable and extremely wear-reducing. Thanks to its optimum viscosity level, enables safe use for both separate and mixture lubrication in the respective specified mixture ratio in air and water-cooled two-stroke engines of land vehicles. Also suitable for use in air-cooled high-performance two-stroke engines in chainsaws.

Note the manufacturer's instructions!

Specifications / Approvals

API TC • Husqvarna • ISO L-EGD • JASO FD

Characteristic data

Density at 15 °C	0,875 g/cm ³ DIN 51757
Viscosity at 40 °C	50 mm ² /s ASTM D 7042-04
Viscosity at 100 °C	9,1 mm ² /s ASTM D 7042-04
Viscosity index	165 DIN ISO 2909
Pour point	-48 °C DIN ISO 3016
Flash point	98 °C DIN ISO 2592
Total base number	2,3 mg KOH/g DIN ISO 3771
Sulfate ash	0,15 g/100g DIN 51575
Color / appearance	red

Available pack sizes

1 l Canister plastic	6523 AR-DE-EN-ES-FR-IT-PT- RO-RU
20 l Canister plastic	8603 DE-EN
60 l Black plate barrel	8830 DE-EN