

Product information

megol Premium Getriebeöl HC GL 4 SAE 75W-80



Description

Gear oil based on HC synthetic technology that is suitable for use in manual transmissions, particularly in manual transmissions with retarder/intarder, non-synchronized manual transmissions, steering systems and auxiliary transmissions. megol Premium Gear Oil HC GL 4 SAE 75W-80 can be used in commercial vehicles – including for extended oil change intervals up to 320,000 km – and cars. It can also be used in cases in which shifting difficulties occur with single-grade oils/higher viscosity API GL-4 products, for example.

Available pack sizes

200 l Black plate barrel 6843
DE-EN

Note the manufacturer's instructions!

Specifications / Approvals

API GL4 • MAN 341 Typ Z4 • ZF TE-ML 01L • ZF TE-ML 02L • ZF TE-ML 16K • ZF approval number ZF008326

Meguin recommends this product for vehicles or assemblies for which the following specifications or original part numbers are required:

DAF • Eaton Extended Drain (300.000 km) • IVECO • MAN 341 Typ E3 • Renault Trucks • Volvo 97305 • ZF TE-ML 08

Characteristic data

SAE class (gear oils)	75W-80 SAE J306
Density at 15 °C	0,86 g/cm ³ DIN 51757
Viscosity at 40 °C	55,8 mm ² /s ASTM D 7042-04
Viscosity at 100 °C	9,5 mm ² /s ASTM D 7042-04
Viscosity at -40 °C (Brookfield)	<= 150000 mPas ASTM D 2983-09
Viscosity index	154 DIN ISO 2909
Pour point	-42 °C DIN ISO 3016
Flash point	240 °C DIN ISO 2592
Color number (ASTM)	L 1,5 DIN ISO 2049

Available pack sizes

20 l Canister plastic 6841
DE-EN