

Product information

Meguin Rostschutz-Sprühoel ohne Graphit



Description

Thin mineral oil with corrosion protection additives that can be easily atomized. It penetrates well into all sheet metal gaps and folds and spreads across the floor of the treated vehicle. The film that forms does not attack rubber parts or noise-dampening bitumen compounds. Its special additives protect sheet metal parts against rust and acts as an anti-squeak fluid between chafing metal parts and spring leaves.

Characteristic data

ISO viscosity class	VG 7 DIN 51519
Density at 15 °C	0,83 g/cm ³ DIN 51757
Viscosity at 20 °C	17,7 mm ² /s ASTM D 7042-04
Viscosity at 40 °C	9,1 mm ² /s ASTM D 7042-04
Viscosity at 100 °C	2,55 °C ASTM D 7042-04
Viscosity index	109 DIN ISO 2909
Pour point	-30 °C DIN ISO 3016
Flash point	150 °C DIN ISO 2592
Neutralization number	0,2 mg KOH/g DIN 51558 T1
Saponification number	1,6 mg KOH/g DIN 51559 T1
Oxide ash	<0,01 g/100g DIN EN ISO 6245
Color number (ASTM)	1 DIN ISO 2049

Available pack sizes

20 l Canister plastic	8753 DE-EN
60 l Black plate barrel	9341 DE-EN
200 l Black plate barrel	8754 DE-EN
1.000 l Deposit container	9691 DE-EN