

Product information

megol Transmission-Fluid ATF III G



Description

Hydraulic fluid for automatic transmissions and hydraulic clutches for which a type Dexron III automatic transmission fluid is prescribed. It guarantees perfect operation of hydraulic transmissions even in the heaviest duty applications and even when exposed to large temperature fluctuations. Also suitable as a hydraulic fluid for systems that work under extreme operating conditions.



Specifications / Approvals

Caterpillar TO-2 • MAN 339 Typ L1 • MAN 339 Typ Z1 • MAN 339 Typ V1 • ZF TE-ML 04D • ZF TE-ML 14A • ZF TE-ML 17C

Available pack sizes

1 l Can plastic	9073
	AR-EN-ES-FR-NL-PT
5 l Canister plastic	9147
	DE-EL-EN-FR-HR-RU

Meguin recommends this product for vehicles or assemblies for which the following specifications or original part numbers are required:

Allison C4 • Allison TES 389 • Dexron II D • Dexron II E • Dexron III G • Dexron III H • Dexron TASA (Typ A/Suffix A) • Ford Mercon • MB 236.1 • MB 236.6 • Voith H55.6335.XX (G 607) • Volvo 97341 • ZF TE-ML 02F • ZF TE-ML 03D • ZF TE-ML 14B • ZF TE-ML 09 • ZF TE-ML 11B • ZF TE-ML 11A

Characteristic data

Density at 15 °C	0,855 g/cm ³ DIN 51757
Viscosity at 40 °C	34,1 mm ² /s ASTM D 7042-04
Viscosity at 100 °C	7,4 mm ² /s ASTM D 7042-04
Viscosity at -40 °C (Brookfield)	<= 20000 mPas ASTM D 2983-09
Viscosity index	192 DIN ISO 2909
Pour point	-45 °C DIN ISO 3016
Flash point	212 °C DIN ISO 2592
Sulfate ash	0,1 g/100g DIN 51575
Shear stability, viscosity at 100 °C after 20 h	5,1 mm ² /s DIN 51350-06-KRL/C
Color number (ASTM)	L 2,5 DIN ISO 2049

Available pack sizes

1 l Can plastic	6839
	AR-DE-EL-EN-FR-RU