

Product information

Meguin Korrosionsschutz 6M



Description

Corrosion inhibitor with dewatering effect. For the preservation of metal parts that are intended for intermediate storage inside for up to six months. Impressive thanks to good anti-corrosion properties in thin layers and the resulting high yield. Is easy to removed, even after six months of storage. Ideally suited for use when processing water-miscible cooling lubricants.

Characteristic data

Base	napht. Basis
Viscosity at 20 °C	1,8 mm ² /s DIN 51562
Viscosity at 40 °C	1 mm ² /s DIN 51562
Density at 20 °C	0,8 g/cm ³ DIN 51757
Flash point	min. 56 °C DIN EN ISO 2719
Protects against corrosion	max. 12 Monate unter Dach max. 6 Monate allgemein
Evaporation residue	8 Gew.-%
solvent	Isoparaffin
Water displacement	<20 s
Color / appearance	clear, brown liquid

Application

Ready-to-use and can be applied by immersion or spraying. Is used undiluted as corrosion inhibitor with water displacing properties mainly with iron, cast iron and steel materials. If the dewatering effect is utilized, the parts should only be immersed (with dry parts, spraying is also possible). Forms an extremely thin, oily film without anti-slip properties on the parts.

Available pack sizes

20 l Canister plastic 9240
DE