

Product information

megol Motorenoel New Engine FE SAE 5W-20



Description

Modern motor oil specially developed for Ford EcoBoost engines. Ensures optimal performance under all operating and load conditions, while providing excellent engine-cleaning properties.

Note manufacturer's instructions!

Specifications / Approvals

ACEA C5 • API SN • Ford WSS-M2C 948-B

Meguin recommends this product for vehicles or assemblies for which the following specifications or original part numbers are required:

Jaguar / Land Rover STJLR.03.5004

Characteristic data

SAE class (engine oils)	5W-20 SAE J 300
Density at 15 °C	0,850 g/cm ³ DIN 51757
Viscosity at 40 °C	46,0 mm ² /s ASTM D7042
Viscosity at 100 °C	8,3 mm ² /s ASTM D7042
Viscosity at -35 °C (MRV)	< 60000 mPas ASTM D4684
Viscosity at -30 °C (CCS)	≤ 6600 mPas ASTM D5293
Viscosity index	160 DIN ISO 2909
HTHS at 150°C	≥ 2,6 mPas ASTM D5481
Pour point	-39 °C DIN ISO 3016
Flash point	220 °C DIN ISO 2592
Evaporation loss (Noack)	11,0 % CEC-L-40-A-93
Total base number	8,5 mg KOH/g DIN ISO 3771
Sulfate ash	≤ 0,8 g/100g DIN 51575
Color number (ASTM)	L 3,5 DIN ISO 2049

Available pack sizes

20 l Canister plastic	9293 DE-EN
60 l Black plate barrel	9295 DE-EN
200 l Black plate barrel	9297 DE-EN
1.000 l Deposit container	9732 DE-EN
1 l Bulk goods	9299 DE

Available pack sizes

5 l Canister plastic	9291 AR-DE-EN-ES-FR-IT-PT- RO-RU
----------------------	--