

Product information

megol Getriebeöl Power Transmission SAE 80W-90



Description

Hypoid gear oil based on selected base oils and the latest additive technology that meets the current requirements of motor vehicle and transmission manufacturers. Thanks to this new additive technology, it can also be used in Mercedes Benz vehicles extended oil change intervals up to 350,000 km.

Specifications / Approvals

API GL5 • API MT-1

Meguin recommends this product for vehicles or assemblies for which the following specifications or original part numbers are required:

ARVIN MERITOR AXLES • MAN 342 Typ M2 • MB 235.0
• MB 235.6 • MB 235.20 • MIL-PRF 2105 E • Scania
STO 1:0 • ZF TE-ML 05A • ZF TE-ML 07A • ZF TE-ML
08 • ZF TE-ML 12E • ZF TE-ML 16B • ZF TE-ML 16C •
ZF TE-ML 16D • ZF TE-ML 17B • ZF TE-ML 19B • ZF
TE-ML 21A

Characteristic data

SAE class (gear oils)	80W-90 SAE J306
Density at 15 °C	0,9 g/cm ³ DIN 51757
Viscosity at 40 °C	140 mm ² /s ASTM D 7042-04
Viscosity at 100 °C	14,6 mm ² /s ASTM D 7042-04
Viscosity at -26 °C (Brookfield)	<= 150000 mPas ASTM D 2983-09
Viscosity index	103 DIN ISO 2909
Pour point	-30 °C DIN ISO 3016
Flash point	210 °C DIN ISO 2592
Color number (ASTM)	L 3,5 DIN ISO 2049

Available pack sizes

20 l Canister plastic 9433
DE-EL-EN-FR-HR-RU