

Product information

megol Spezial MTF GL5 SAE 75W-80



Description

Specially developed gear oil that is primarily characterized in that it enables easy and precise shifting operations in the transmission, even at low temperatures and under heavy load. This product was developed specially for Peugeot and Citroën manual transmissions and can also be used as a problem solver in the event of noise generation and shifting difficulties for manual transmissions from other manufacturers.



Specifications / Approvals

API GL5

Meguin recommends this product for vehicles or assemblies for which the following specifications or original part numbers are required:

MIL-L 2105 C • Peugeot Citroen (PSA) B71 2315 •
Peugeot Citroen (PSA) B71 2330

Characteristic data

SAE class (gear oils)	75W-80 SAE J306
Density at 15 °C	0,870 g/cm ³ DIN 51757
Viscosity at 40 °C	61,0 mm ² /s ASTM D 7042-04
Viscosity at 100 °C	9,7 mm ² /s ASTM D 7042-04
Viscosity at -40 °C (Brookfield)	≤ 150000 mPas ASTM D 2983-09
Viscosity index	140 DIN ISO 2909
Pour point	-42 °C DIN ISO 3016
Flash point	210 °C DIN ISO 2592
Color number (ASTM)	L2,5 DIN ISO 2049

Available pack sizes

1 l Can plastic 9435
DE-EL-EN-FR-HR-RU