

Product information

megol Motorenoel Fuel Economy SAE 5W-30



Description

High performance motor oil based on HC synthetic technology with a latest generation additive system (Low-SAPS technology and reduced HTHS). Meets the high performance requirements of modern gasoline and diesel engines and ensures maximum service life of the diesel particulate filter as well as low wear, good engine cleanliness and long oil change intervals.

Application: Passenger cars

SAPS level: Low-SAPS

Note manufacturer's instructions!

Specifications / Approvals

ACEA C2 • ACEA C3 • API SP • MB-Approval 226.52 • MB-Approval 229.52 • Peugeot Citroen (PSA) B71 2290 • Renault RN 17

Meguin recommends this product for vehicles or assemblies for which the following specifications or original part numbers are required:

Fiat 9.55535-S1 • Honda • Mazda • Toyota

Characteristic data

SAE class (engine oils)	5W-30 SAE J300
Density at 15 °C	0,855 g/cm ³ DIN 51757
Viscosity at 40 °C	73,0 mm ² /s ASTM D7042
Viscosity at 100 °C	12,4 mm ² /s ASTM D7042
Viscosity at -30 °C (CCS)	≤ 6600 mPas ASTM D5293
Viscosity at -35 °C (MRV)	< 60000 mPas ASTM D4684
Viscosity index	165 DIN ISO 2909
HTHS at 150°C	≥ 3,5 mPas ASTM D5481
Pour point	-39 °C DIN ISO 3016
Flash point	230 °C DIN ISO 2592
Evaporation loss (Noack)	9,7 % CEC-L-40-A-93
Total base number	8,5 mg KOH/g DIN ISO 3771

Characteristic data

Sulfate ash	≤ 0,8 g/100g DIN 51575
Color number (ASTM)	L 3,0 DIN ISO 2049

Available pack sizes

1 l Canister plastic	9440 AR-DE-EN-ES-FR-IT-PT-RO-RU
5 l Canister plastic	9441 AR-DE-EN-ES-FR-IT-PT-RO-RU
20 l Canister plastic	9442 DE-EN
60 l Black plate barrel	9443 DE-EN
200 l Black plate barrel	9444 DE-EN
1.000 l Deposit container	9735 DE-EN
1 l Bulk goods	9445 DE