

Product information

megol Super Traktorenoel STOU SAE 10W-40



Description

Universal oil STOU (Super Tractor Oil Universal) specially developed for agricultural machines. Optimally tailored to agricultural machinery, the product combines the properties of an outstanding motor oil with the requirements of different tractor specifications for manual and axle transmissions, hydraulic systems, fluid flywheels and wet brakes.

Specifications / Approvals

ACEA E2 • ACEA E3 • API CF-4 • API CG-4 • API SF • API GL4

Meguin recommends this product for vehicles or assemblies for which the following specifications or original part numbers are required:

Allison C4 • Case (IHC) B6 • Caterpillar TO-2 • David Brown • Fendt • John Deere J27 • KHD • Mack EO-K • Mack EO-K2 • Massey-Ferguson M1139 • Massey-Ferguson M1144 • Massey-Ferguson M1145 • MB 227.1 • MB 228.1 • MIL-L 2104 D • MIL-L 2105 • MIL-L 46152 C • ZF TE-ML 06B • ZF TE-ML 07B • Ford New Holland M2C 84-A • Ford New Holland M2C 159-B • Ford New Holland M2C 159-C • Steyr

Available pack sizes

20 l Canister plastic	9447 DE-EN
60 l Black plate barrel	9448 DE-EN
200 l Black plate barrel	9449 DE-EN
1 l Bulk goods	9450 DE

Characteristic data

Viscosity SAE class	10W-40 SAE J300
Density at 15 °C	0,86 g/cm ³ DIN 51757
Viscosity at 40 °C	92 mm ² /s ASTM D 7042-04
Viscosity at 100 °C	14 mm ² /s ASTM D 7042-04
Viscosity at -25 °C (CCS)	≤ 7000 mPas ASTM D 5293
Viscosity index	156 DIN ISO 2909
Pour point	-36 °C DIN ISO 3016
Evaporation loss (Noack)	12 % CEC-L-40-A-93
Flash point	230 °C DIN ISO 2592
Total base number	11,2 mg KOH/g DIN ISO 3771
Sulfate ash	1,6 g/100g DIN 51575
Color number (ASTM)	3 DIN ISO 2049