

Product information

megol Motorenoel UHPD Truck SAE 5W-30



Description

The latest generation of low-friction motor oil. Due to its outstanding properties, it is suitable for use in all commercial vehicle diesel engines under all operating conditions and all environmental influences (all-season oil). The use of state-of-the-art additives in combination with HC synthetic oils guarantees optimum wear protection and enables maximum oil change intervals. It is mixable with all commercially available motor oils. Recommended for use in diesel engines only!

Note the vehicle manufacturers' instructions for extended oil change intervals!

Specifications / Approvals

ACEA E4 • ACEA E7 • Mack EO-N • MAN M 3277 • MB-Approval 228.5 • Renault Trucks RLD-2 • Scania LDF-3 • Volvo VDS-3

Meguin recommends this product for vehicles or assemblies for which the following specifications or original part numbers are required:

API CF • DAF • IVECO 18-1804 • MTU Typ 3 • Renault Trucks RD-2 • Renault Trucks RLD • Renault Trucks RXD

Characteristic data

Sulfate ash	<= 2,0 g/100g DIN 51575
Color number (ASTM)	L4,0 DIN ISO 2049

Available pack sizes

20 l Canister plastic	9492 DE-EN
200 l Black plate barrel	9490 DE-EN

Characteristic data

SAE class (engine oils)	5W-30 SAE J300
Density at 15 °C	0,86 g/cm ³ DIN 51757
Viscosity at 40 °C	70 mm ² /s ASTM D 7042-04
Viscosity at 100 °C	12 mm ² /s ASTM D 7042-04
Viscosity at -35 °C (MRV)	< 60000 mPas ASTM D4684
Viscosity at -30 °C (CCS)	<= 6600 mPas ASTM D5293
Viscosity index	169 DIN ISO 2909
HTHS at 150°C	>= 3,5 mPas ASTM D5481
Pour point	-48 °C DIN ISO 3016
Evaporation loss (Noack)	12 % CEC-L-40-A-93
Flash point	224 °C DIN ISO 2592
Total base number	15,4 mg KOH/g DIN ISO 3771